Government of India-Ministry of Railways Research Designs & Standards Organisation Lucknow - 226 011 DID (0522) 2450115 DID (0522) 2465310



No. CT/USFD/ACS

Dated:

.09.2018

I. The General Manager (Engg./Works)

- 1. Central Railway, CST, Mumbai 400 001.
- 2. Eastern Railway, Fairlie Place, Calcutta 700 001.
- 3. East Central Railway, Hajipur 844 101.
- 4. East Coast Railway, Chandrasekharpur, Bhubaneshwar 751 016.
- 5. Northern Railway, Baroda House, New Delhi 110 001.
- 6. North Central Railway, Allahabad 211 001.
- 7. N.E.Railway, Gorakhpur 273 001.
- 8. N.F.Railway, Maligaon, Guwahati 781 011.
- 9. North Western Railway, Jaipur 302 001.
- 10. Southern Railway, Park Town, Chennai 600 003.
- 11. S.C.Railway, Rail Nilayam, Secunderabad 500 371.
- 12. S.E.Railway, Garden Reach, Calcutta 700 043.
- 13. South East Central Railway, Bilaspur 495 004
- 14. South Western Railway, Hubli- 580 023.
- 15. Western Railway, Churchgate, Mumbai 400 020
- 16. West Central Railway, Jabalpur 482 001

Sub: Manual for Ultrasonic testing of Rails and Welds (Revised 2012) - A & C Slip No. 04 of September, 2018

- Ref: (i) This office letter of even no.dt: 10.08.2016
 - (ii) Railway Board's letter no. Track/21/2007/0903/7 dt: 20.08.2018
- 1. The Revised A&C Slip No. 3 of August, 2016 to 'Manual for Ultrasonic testing of Rails and Welds, (Revised 2012)' was circulated to all Zonal Railways vide this office letter at reference (i) above.

Please find enclosed herewith A&C Slip No. 04 of September, 2018 to the above Manual duly approved by Railway Board for information and further necessary action.

2. The Correction Slip to USFD Manual is being issued in view of Railway Board's orders on following items of 86th TSC meeting and 9th extraordinary TSC meeting.

S No.	Item no.	Description of Item
1	1303	Test free period of USFD testing of rails

3. Apart from the above as a trial preventive measure to reduce the number of rail failures during reduced testing frequency period and weld failure in initial period, additional Policy Instructions on Ultrasonic testing of rails & welds to be read in conjunction with Manual for Ultrasonic testing of rails & welds (Revised-2012) are also enclosed, which are valid for two years i.e. up to 31.08.2020.

Zonal Railways are also requested to send the feedback to RDSO alongwith data analysis for the impact of additional policy instruction on reduction of early rail and weld failures and impact on work load.

4. Please acknowledge the receipt.

संलग्न-उपरोक्त।

(नीलमणि)
कार्यकारी निदेशक/रेलपथ—1
कृते महानिदेशक/रेलपथ

- Copy along with a copy of the A & C Slip No. 04 of September, 2018 for information II and record to:
 - The General Manager(Cons.), N.F. Railway, Maligaon, Guwahati-781 011. 1.
 - The Chief Commissioner of Railway Safety, Ministry of Tourism & Civil Aviation, 2. NE Rly. Compound, 16-A, Ashok Marg, Lucknow260 001.
 - The CMD, Managing Director, KRCL, Belapur Bhawan, Plot No.6,CBD, Belapur, 3. New Bombay-400 614.
 - The Director General, Railway Staff College, Vadodara-390 004. 4.
 - The Director, IRICEN, Pune-411 001. 5.
 - The Executive Director, IRCAMTECH, Maharajpur Gwalior-474 020 6.
 - ED/M&C/RDSO/Lucknow. 7.
 - ED/QA(Civil), RDSO, Lucknow. 8.
- Copy along with a copy of A&C Slip No. 04 of September, 2018 to Executive III Director/Track (Procurement), Railway Board, Rail Bhavan, New Delhi 110 001 for kind information in reference to Railway Board's letter no Track/21/2007/0903/7 dtd 20.08.2018.

संलग्न-उपरोक्त।

(नीलमणि) कार्यकारी निदेशक / रेलपथ-1 कृते महानिदेशक / रेलपथ

Copy along with a copy of the A & C Slip No. 04 of September, 2018 for information IV and record to:

The Chief Safety Officer:

- Central Railway, CST, Mumbai 400 001. 1.
- Eastern Railway, Fairlie Place, Calcutta 700 001. 2.
- East Central Railway, Hajipur 844 101. 3.
- East Coast Railway, Chandrasekharpur, Bhubaneshwar 751 016. 4.
- Northern Railway, Baroda House, New Delhi 110 001. 5.
- North Central Railway, Allahabad 211 001. 6.
- N.E. Railway, Gorakhpur 273 001. 7.
- N.F. Railway, Maligaon, Guwahati 781 011. 8.
- North Western Railway, Jaipur 302 001. 9.
- Southern Railway, Park Town, Chennai 600 003. 10.
- S.C.Railway, Rail Nilayam, Secunderabad 500 371. 11.
- S.E. Railway, Garden Reach, Calcutta 700 043. 12.
- South East Central Railway, Bilaspur 495 004 13.
- South Western Railway, Hubli- 580 023. 14.
- Western Railway, Churchgate, Mumbai 400 020 15.
- West Central Railway, Jabalpur 482 001. 16.

Copy alongwith a copy of the correction slip No. 04 of September 2018 for information and record to:

- AED/M&C/RDSO/Lucknow i)
- ED/QA(Civil), RDSO, Lucknow ii)

संलग्न-उपरोक्त।

(नीलमणि) कार्यकारी निदेशक / रेलपथ-1 कृते महानिदेशक / रेलपथ

'Manual for Ultrasonic testing of rails & welds, (Revised-2012)'

A & C Slip No. 4 of September, 2018

- 1. Para 6.6 is modified as under:
- 6.6 **Frequency of testing of rails and welds**: In view of the revised criteria of defect mentioned in Para 6.2, the testing frequency of 8 GMT has been prescribed. Based on the same, testing schedule of rails/welds as laid down in Para 6.6.1.1 shall be followed.
- 6.6.1 After the initial USFD testing of rails in rail manufacturing plant, the subsequent USFD testing needs to be carried out at reduced frequency until the rail have undergone 15% of the service life in GMT as given below (para 302(i) (d) of IRPWM):

For rails rolled in April 1999 and later, the reduced frequency testing period shall be 25% instead of 15%.

Gauge	Rail Section	Assessed GMT service life for T- 12 72 UTS rails	Assessed GMT service life for T- 12 90 UTS rails
B.G.	60Kg	550	800
	52Kg	lier odocine de 350 noi emici esole	525
	90 R	250	375 as ad Bade
M.G.	75 R	150	inchektow TA to united C21.2
	60 R	ed elder edt al m 125 mans kennelber	and calibration as per references

Rail testing during reduced frequency testing period is to be done using all probes (as given in para 4.1) as is being done during normal testing frequency period on passage of every 40 GMT traffic or Eight (08) years, whichever is earlier.

Whenever, rails are not tested in rail manufacturing plant, the reduced frequency testing period shall not be applicable and the rail testing shall be done immediately after its laying in field and thereafter at the periodicity given in table under para 6.6.1.1.

- 2. Para 8.14 is modified as follows:
- 8.14 Action to be taken after detection of defects in AT welds: Action to be taken for defects in AT welds shall be same as at para 6.4. In addition, following shall also be applicable for welds classified as defective (DFWO/DFWR) in Initial acceptance test & periodic testing of AT welds using hand probing:

Г	C1 'C -4'	Dainting on both	Action to be taken
	Classification	Painting on both	Notion to be taken
1		faces of weld (In	sdong
		Head)	(') I CDCWO wold following action will be taken:
	the result of the second secon		(i)In case of DFWO weld, following action will be taken:
	DFWO/DFW	one circle with red	A CORVER ON WAY AVECTOR about improve amond materiation of 20 kmph
	R' with	paint.	a) SSE/JE (P.Way)/USFD shall impose speed restriction of 30 kmph
	$0^{0} / 2MHz,$	In case of DFWR,	
	$70^{\circ}/ 2MHz, 45^{\circ}/$	two cross with red	about the flaw location, who shall ensure the following:
1	$2 \text{ MHz or } 70^{\circ}$	paint.	b) Protection of defective weld by joggled fish plates using
	2MHz SL	spel and entered to sho	minimum two tight clamps immediately with a speed restriction of
	probe, $45^{\circ}/2$		30 kmph. Speed restriction can be relaxed to normal after
	MHz Tandem	An a same	protection of DFWO weld by joggled fish plates with 2 far end
	Rig	U6 ≥ V6	tight bolts (one on each side) with champhering of holes, within 3
9		245 ≤ 60	days. The joint is to be kept under observation.
31		24 > 05 K	(ii) In case of DFWR following action will be taken:
		06221	a) SSE/JE (P.Way) USFD shall impose speed restriction of 30kmph
		4140	or stricter immediately and communicate to sectional SSE/JE
		ne (alife rathin an of)	about the flaw location who shall ensure the following:
		e ni sone na Mallo soni a	b) Protection of DFWR weld by joggled fish plates using minimum
		CHARLES CONT.	two tight clamps immediately. SR of 30 Kmph can be relaxed to
		AND ALTERNATION OF THE STATE OF	normal after providing joggled fish plates with two far end tight
			bolts one on each side with champhering of holes. The DFWR
MI		boother of blook et	weld shall be replaced within three months of detection.
		actures of defective we	Adequate traffic block should be granted for removal of DFWR
	1		welds. In case of non removal within three months, a speed
	10 X 10 X		restriction of 75 kmph for loaded goods train and 100 kmph for
	7// \ \ 10 A		

2 weigs, (Accessed 12)	passenger train should be imposed. (iii) In case of defective weld (DFWO/DFWR) on major bridges & bridge approaches (100m either side) and in tunnels & on tunnel approaches (100m either side), following action will be taken:
revised enteria of defect mentioned as ed on the same, testing schedule of rails	a) SE/JE(P.Way)/USFD shall impose speed restriction of 30 Kmph or stricter immediately and to be continued till defective weld is replaced. He should communicate to sectional SE/JE (P.Way) about the flaw location who shall ensure the following:
g plant, the subsequent USFD testing a creame 15% of the service tife in GMF.	b) Protection of defective weld using clamped joggled fish plate within 24 hrs.c) The defective weld shall bereplaced within 3 days of detection.

Note: DFWR and DFWO found in "Initial Acceptance Test" shall be removed from track as per para 8.10.1.

- 3. Para 8.15, 8.15.1 and 8.15.2 has been modified as under:
- 8.15 Frequency of testing of welded joints
- **8.15.1** Frequency of testing of welded joints for through periodic rail testing by SRT/DRT using 0° & 70° probes shall be as per 6.6.1.1.

8.15.2 Testing of AT welded joints by hand probing shall comprise of testing by probes with sensitivity setting and calibration as per references indicated against them in the table below:

S.No	Probes	Calibration as per	Sensitivity Setting as per	Scanned area	Acceptance Criteria
1.	0^{0} 2 MHz	Para 8.5.1	Para 8.5.2, Fig 20(a)	Head, web	As per Para 8.5.4
2.	70° 2MHz	Para 8.6.1, 8.9.1	Para 8.6.2, 8.9.2, Fig 20(a)	Head, weld foot	As per Para 8.6.4 & 8.9.4
3.	70° 2MHz SL	Para 8.8.1	Para 8.8.2, Fig 22 (a)	Weld foot (Half Moon Defect)	As per Para 8.8.4
4.	45°2 MHz	Para 8.7.1	Para 8.7.1.2 , Fig 22 (a) & 23	Weld foot (Half Moon Defect/clustered defect & micro porosity)	As per Para 8.7.1.4
5.	45° 2 MHz single crystal probe	As per Para 8.7.2.1	As per Para 8.7.2.2	Lack of fusion in the web and foot region below web	As per Para 8.7.2.4

The frequency of testing of AT welds with above listed probes by hand probing shall be as under:

SNo	Type of Welds	Type of Testing	Testing Schedule Every 40 GMT or 5 years whichever is earlier Immediately after welding	
1	Conventional AT weld	Periodic Tests Acceptance Test		
2				
3	PAUL SOLD DISK 5	First Periodic Test	1 year	
	SKV Weld	Further tests based on route	Routes having GMT	Frequency
4	n des lesiones et Me	GMT	> 80	1 years
5	markanteda dire (edis	tone to one shed his in	>60 ≤ 80	1½years
6	o isa tozda tobila igaj	of at at thing of Cores to be	>45 ≤ 60	2 years
7	ar of life enion pull	oilat XWRG to see at the	>30 ≤ 45	3 years
8	i banga pangsai (les	SSEAR ON WAY THE	> 15 ≤30	4 years
9	alazimummea fana	Considerated internalisation	0-15	5 years

In case of welds on major bridges & bridge approaches (100m either side) and in tunnels & on tunnel approaches (100m either side), the minimum frequency of testing shall be once in a year.

Due to unusually high weld failure or other abnormal development in some sections, Chief Engineer may order testing of welds early, as per need.

The testing interval of USFD testing of defective AT welds should be reduced by 50% of normal testing interval of AT welds as provided in para 8.15.1 to avoid fractures of defective welds.



'Additional Policy Instructions on Ultrasonic testing of rails & welds, to be read in conjunction with Manual for Ultrasonic testing of rails & welds (Revised-2012)'

- 1. Frequency of testing of rails and AT welds has been prescribed in Para 6.6 and 8.15.2 respectively of Manual for Ultrasonic testing of rails & welds (Revised-2012). As a trial preventive measure to reduce the number of rail failures during reduced testing frequency period and weld failures in initial period, Ultrasonic testing of rails and welds shall be done at frequency prescribed below. This will be valid for a period of two years, i.e. upto 31.08.2020.
- 1.1 Frequency of USFD for all BG and MG routes shall be as under in place of table given in **Para 6.6.1.1**of Manual. For other sections, Chief Engineer of the Railway may adopt a frequency at his discretion.

A	В	С	D	
Route	Route having	USFD Testing Frequency during	USFD Testing Frequency	
	GMT	the "Reduced frequency testing	(Other than during reduced	
		Period" (As defined in Para	frequency testing period) once	
		6.6.1), once in	in	
All MG	< 2.5	8years	5 years	
routes	2.5 - 5.0	4years	3 years	
	> 5	3years	2 years	
All BG	<u>< 5</u>	4 years	2 years	
routes	routes $> 5 \le 8$ 30 Months $> 8 \le 12$ 20 Months $> 12 \le 16$ 15 Months		12 months	
			9 months	
			6 months	
	> 16 ≤ 24	10 Months	4 months	
$> 24 \le 40$ 6 Me		6 Months	3 months	
	$> 40 \le 60$ 4 Months 2		2 months	
	0.1.20.1.1.2		1½ months	
			1 month	

- 1.2 Frequency of USFD testing during reduced frequency testing period is broadly based on the criteria of:-
 - (a) Passage of every 20 GMT traffic during reduced frequency testing period; or
 - (b) Eight (08) years, whichever is earlier
- 2. Frequency of testing of AT welds by hand probing with probes listed in Para 8.15.2 of Manual shall be as under:

S No	Type of Welds	Type of Testing	Testing Schedule	
1	Conventional	Periodic Tests	Every 40 GMT or 5 years	
	AT weld	*	whichever is	earlier
2		Acceptance Test	Immediately after	r welding
3		First Periodic Test	20 GMT or 1 year whichever is earlier	
	SKV Weld			
		Further tests based on route	Routes having GMT	Frequency
4		GMT	> 80	1 years
5			>60 ≤ 80	1½years
6			>45 < 60	2 years
7			>30 ≤ 45	3 years
8			> 15 ≤30	4 years
9	-1		0-15	5 years

